

Good Practice - Oil Contaminated Cargoes for Transportation by OSV



TO BE COMPLETED AND PROVIDED TO OSV MASTER PRIOR TO BACK LOADING.

APPENDIX II ANALYSIS FORM

Sample Description				
Sample Reference				
Vessel		Date		
Offshore Asset		Producer		
Total number of Barrels		Waste Note		
Component name	Value	Units	Method	MSDS Available
		% volume	N/A	
		% volume	N/A	
		% volume	N/A	
		% volume	N/A	
		% volume	N/A	
		% volume	N/A	
		% volume	N/A	
		% volume	N/A	
pH			pH Meter	
Salinity (Chloride) (mg/l)		mg/l	Titration	
Flash Point (Oil Fraction)		°C	Closed Cup Flash Point	>60°C
Base Oil Flash Point		°C	Closed Cup Flash Point	From MSDS
Other low Flash point chemical		°C	Closed Cup Flash Point	From MSDS
Gas Test (H2S)		Mg/l	Gas Meter	Zero mg/l
Gas Test (LEL)		%		<25%
Gas Test (Oxygen)		%		
Water		% volume	Retort	
Oil Content		% volume	Retort	
Solids		% volume	Retort	
Bulk Specific Gravity		S. G.		<2.5
Appearance				
Odour				
Conclusions				
Analyst (print name)				Issue 2
Analyst signature				May 19 2004
Date				